



ACCESS, CHECK & ASSEMBLE

STEPS 01-04

PT-402 vertical service tower / removable lower collar / two tunnel ends

USE ONLY LABEL-AUTHORIZED BAIT / FOLLOW THE BAIT LABEL, SITE PLAN AND REQUIRED PPE

01 CHECK BODY & SERVICE COLLAR



ACTION

Wear the PPE required by the bait label. Confirm the housing, upper cap/lock and supplied curved lower service sleeve/collar are present, clean and undamaged.

KEY CHECK

All supplied parts present; shell sound

02 IDENTIFY BOTH SERVICE POINTS



ACTION

Set the empty station upright on a stable work surface. Locate the recessed upper lock and the removable lower service collar shown with the product.

KEY CHECK

Upper lock and lower collar identified

03 ACCESS & CHECK SUPPLIED PARTS



ACTION

Use only the matching service tool and the factory-approved opening procedure supplied with the station. Keep the sleeve/collar and every supplied service part together; do not force or substitute parts.

KEY CHECK

Supplied parts confirmed; nothing forced

04 CHECK & REFIT THE LOWER COLLAR



ACTION

Inspect the removed lower service collar and its mating service area shown with the station. Refit the collar only by the factory-approved procedure, seat it fully and verify it is flush; do not force it.

KEY CHECK

Collar seated flush; tunnel unobstructed



STRUCTURE CHECK / PT-402

Confirm the upper lock, lower service collar and two tunnel ends match the exact product views before use.

BAIT REQUIREMENT: follow the bait label and use only the supplied holder or factory-approved production pack-out. Never drop loose bait into the tower or tunnel.



CLOSE, PLACE & SERVICE

STEPS 05-08

PT-402 vertical service tower / removable lower collar / two tunnel ends

USE ONLY LABEL-AUTHORIZED BAIT / FOLLOW THE BAIT LABEL, SITE PLAN AND REQUIRED PPE

05 CLOSE, LOCK & PULL-CHECK



ACTION

Seat the cap fully, engage the lock with the matching service tool and remove the tool. Pull-check the cap gently; do not place an unlocked station.

KEY CHECK

Cap seated; lock engaged

06 PLACE ON THE ROUTE



ACTION

Place the assembled station upright on a stable surface, with the horizontal tunnel parallel to the identified rodent travel line and the tower easy to service.

KEY CHECK

Stable, upright and accessible

07 KEEP BOTH ENDS CLEAR



ACTION

Check both tunnel openings from end level. Keep them free of walls, debris, stored goods and vegetation, subject to the bait label and site plan.

KEY CHECK

Two clear approaches

08 INSPECT & SERVICE



ACTION

Open only at the interval required by the bait label and site plan. Check bait condition, blockage, moisture and damage; clean, dry, reload as allowed and relock.

KEY CHECK

Condition recorded; station relocked

SERVICE & SAFETY

Keep the station, bait and service tool away from children, pets, food, feed and non-target animals as required by the bait label. Do not handle bait with bare hands. Do not guess bait quantity, spacing, inspection frequency or permitted location. Remove bait and contaminated material according to the bait label and local requirements. Clean and dry the housing before reloading; never place a damaged or unlocked station.