



CHECK, SEAT THE PAVER & OPEN

STEPS 01-04

PT-404PV Plastic Rat Bait Station with Paver / PT-404 upper station / independent slide-in weighted paver tray / metal bait-retaining rods

USE ONLY LABEL-AUTHORIZED BAIT / FOLLOW THE BAIT LABEL, SITE PLAN AND REQUIRED PPE

01 CHECK ALL COMPONENTS



ACTION

Wear the PPE required by the bait label. Check the upper station, supplied key, metal bait rods, lower tray and paver slab. Do not use cracked, distorted or incomplete parts.

KEY CHECK

Station, key, rods, tray and paver present

02 INSPECT THE PAVER TRAY



ACTION

Slide the lower paver tray outward only far enough to inspect it. Confirm the slab sits flat and the tray and guide rails are undamaged and free of debris.

KEY CHECK

Paver flat; tray and rails sound

03 SEAT THE PAVER MODULE



ACTION

Support the station and push the loaded paver tray straight into the lower rails until it is fully seated. Keep fingers clear of the closing gap and do not force it.

KEY CHECK

Tray flush beneath the station

04 UNLOCK & OPEN



ACTION

Insert the supplied key, release the lid catch and raise the upper station lid. Check that the central route, both arched entries, dividers and retaining rods are clear.

KEY CHECK

Upper interior clean and unobstructed

PAVER MODULE

The lower slide-in tray and paver slab form an independent weighted base component. It is not a glue tray and contains no bait, chemical or adhesive. Seat it fully before moving or placing the station.



VERIFY, LOCK, PLACE & SERVICE

STEPS 05-08

PT-404PV Plastic Rat Bait Station with Paver / PT-404 upper station / independent slide-in weighted paver tray / metal bait-retaining rods

USE ONLY LABEL-AUTHORIZED BAIT / FOLLOW THE BAIT LABEL, SITE PLAN AND REQUIRED PPE

05 VERIFY THE RETAINING RODS



ACTION

Confirm the vertical metal rods are present and use them to retain only label-authorized centre-hole bait blocks. Follow the bait label and site plan for bait and quantity; never leave loose bait.

KEY CHECK

Every block retained on a rod

06 CLOSE & LOCK



ACTION

Lower the upper lid, engage the lock with the supplied key and remove the key. Confirm the lid is secure and the paver tray remains fully seated before moving the unit.

KEY CHECK

Lid locked; key removed; tray flush

07 PLACE THE UNIT



ACTION

Set the complete weighted unit on a stable surface as directed by the site plan. Keep both arched entries clear and do not place the unit with the paver tray extended.

KEY CHECK

Unit stable; tray seated; entries clear

08 INSPECT & SERVICE



ACTION

At the interval required by the bait label and site plan, inspect bait, upper housing, paver slab, tray and rails. Remove debris safely, service only as allowed and relock after work.

KEY CHECK

Condition recorded; complete unit relocked

SERVICE & SAFETY

Keep bait, the serviced station and the key managed as required by the bait label and site plan. Do not handle bait with bare hands. Inspect the paver slab, tray and rails as well as the upper housing; remove debris and waste safely; replace damaged parts; and relock after every service. The empty station itself is not represented as child-safe, pet-safe, tamper-resistant or weather-resistant without the required certification.