



PRODUCT PROFILE

SQUIRREL & RAT CAGE TRAP

Single spring-assisted sliding door / top trigger housing / rear treadle



QUICK SPECIFICATION

STANDARD PRODUCT DATA

MATERIAL

Galvanized steel

PRODUCT SIZE

41 x 15.5 x 17 cm

UNIT WEIGHT

1,220 g

PACKING

Bulk packing - 6 pcs/master carton

MASTER CARTON

54 x 44.5 x 41 cm

CARTON WEIGHT

9.90 kg (declared carton weight)

MOQ

1,008 pcs

LEAD TIME

25 days

PT-602 / SQUIRREL & RAT CAGE TRAP

MECHANISM NOTE

The central curved wire is the carry handle. The separate solid end panel is the single sliding door; do not confuse it with PT-601's external setting wire.

01 41 CM CAGE

A longer galvanized wire enclosure for rat and squirrel live-cage applications.

02 TOP TRIGGER HOUSING

The black adjustment knob, trigger housing and linkage remain accessible above the solid top panel.

03 REAR TREADLE + HANDLE

The treadle is positioned opposite the entrance; the curved centre handle keeps the empty trap level in handling.



PRODUCT DETAIL

BUILT AROUND ITS OWN MECHANISM

For professional or property-maintenance live-cage programs where a longer single-door format is required. Keep the solid door, spring, linkage and rear treadle unobstructed.



RAISED DOOR

Single solid sliding door and return spring



TRIGGER PATH

Rear treadle connected to the top linkage



DOOR END

Solid door panel within two side guides

ORDER BASIS

Bulk packing - 6 pcs/master carton / MOQ 1,008 pcs / Lead time 25 days

Logo, carton marks and final production details are agreed with the confirmed order.

PACKING & CONTAINER PLANNING

BULK PACKING BASIS

6 traps are packed directly in one master carton. No individual retail color box is included.



1.2 x 1.0 m PALLET



20' GP



40' GP



40' HQ

CONTAINER	FLOOR LOADING	PALLET LOADING
20' GP	250 ctn / 1,500 pcs 10 x 5 x 5	200 ctn / 1,200 pcs 10 pallets x 4/layer x 5
40' GP	550 ctn / 3,300 pcs 22 x 5 x 5	400 ctn / 2,400 pcs 20 pallets x 4/layer x 5
40' HQ	660 ctn / 3,960 pcs 22 x 5 x 6	400 ctn / 2,400 pcs 20 pallets x 4/layer x 5

Nominal basis: cartons upright; door heights 2,280 mm GP / 2,585 mm HQ; pallet 1,200 x 1,000 x 144 mm; 10 / 20 / 20 pallets. Trial load and carrier confirmation required.