



PT-605

MULTI-CATCH CHIPMUNK & RAT CAGE TRAP

Black expanded-metal cage / dual entry tunnels / top and side service access

PRODUCT-SPECIFIC CONSTRUCTION

BLACK EXPANDED-METAL BODY

The visible black diamond-mesh construction is declared as galvanized steel in the product data.

TWO OPPOSING ENTRIES

Two one-way entry tunnels approach the central floor from opposite sides.

LARGE TOP SERVICE DOOR

The broad rectangular top opening gives direct access to the centre floor for baiting and inspection.

SEPARATE SIDE ACCESS


A distinct side service door is visible in the supplied product views and uses its own fitted latch.

8 CM LOW PROFILE

The 38 x 38 cm square footprint is held to an 8 cm product height for ground-level placement.




PT-605 / PRODUCT BODY AND FITTED OPERATING STRUCTURE



SIDE ACCESS

Separate service door shown open



SERVICE STRUCTURE

Top opening and entry-tunnel geometry



EXPANDED-METAL BODY

Black diamond mesh and reinforced frame

TARGET FORMAT

LIVE CATCH

MATERIAL

GALVANIZED STEEL

PRODUCT SIZE

38 X 38 X 8 CM

UNIT WEIGHT

1.30 KG

MASTER CARTON

6 PCS

STANDARD SUPPLY FORMAT

BULK PACKING / 6 PCS PER MASTER CARTON



PRODUCT & EXPORT PLAN

Declared product data, master packing and conservative upright loading plans.

6

PIECES / MASTER CARTON

7.8


KG NET / MASTER CARTON

8.8

KG GROSS / MASTER CARTON


STANDARD PRODUCT & ORDER DATA

ITEM NO.	PT-605
PRODUCT	Multi Catch Chipmunk & Rat Cage Trap
MATERIAL	Galvanized steel
PRODUCT SIZE	38 x 38 x 8 cm
UNIT WEIGHT	1.30 kg
PACKING	Bulk packing / 6 pcs per master carton
MASTER CARTON	39 x 39 x 49 cm
CARTON N.W. / G.W.	7.8 kg / 8.8 kg
MOQ	600 pcs
REFERENCE LEAD TIME	35 days / subject to order confirmation



PRODUCT FORMAT

dual entries / top door / separate side access



OPERATING DETAIL

Separate service door shown open

PACKING BASIS

Units share the master carton; no individual colour box is included in the declared bulk packout.

EXPORT LOADING - MASTER CARTONS / PRODUCTS

1,200 x 1,000 x 144 mm pallet / nominal container-door basis



PALLET

6 CTN / LAYER



20' GP

10 PALLETS



40' GP

20 PALLETS



40' HQ

20 PALLETS

CONTAINER	FLOOR LOADED	PALLETIZED
20' GP	360 CTN 2,160 products	240 CTN 1,440 products
40' GP	720 CTN 4,320 products	480 CTN 2,880 products
40' HQ	900 CTN 5,400 products	480 CTN 2,880 products

Floor plans: 15 x 6 x 4 / 30 x 6 x 4 / 30 x 6 x 5 cartons, kept upright. Build heights: 1960 / 1960 / 2450 mm.

Pallet plan: 6 cartons/layer; 4 / 4 / 4 layers. Loaded heights: 2104 / 2104 / 2104 mm.

Nominal pallet door clearance: 176 / 176 / 481 mm for 20' GP / 40' GP / 40' HQ.

Planning values use nominal carton and equipment dimensions. Confirm actual door opening, carton tolerance, payload, pallets, restraint and a physical trial load.