

PT-802

FLY / MOSQUITO LIGHT TRAP - LITE

Physical power button and manual slider / USB-C input / illuminated upper intake / vented lower housing

PRODUCT-SPECIFIC CONSTRUCTION

LITE MANUAL CONTROL TOP

A round physical power button and adjacent slider identify the PT-802 control layout.

ILLUMINATED UPPER INTAKE

The light ring, open radial intake and central fan path are visible when the unit is operating.

USB-C INPUT

A side USB-C input supports connection to a compatible supply matching the product rating.

VENTED LOWER HOUSING

Vertical openings around the lower body support the documented airflow and collection path.

INDIVIDUAL COLOUR BOX

Each unit is supplied in one colour box, with 12 boxed units packed in the master carton.



PT-802 / ONE BOXED UNIT / STANDARD PRODUCT CONFIGURATION



PHYSICAL CONTROLS
Round button + manual slider



USB-C INPUT
Supply must match the product marking



LOWER VENTED HOUSING
Keep every opening unobstructed

FORMAT	MATERIAL	PRODUCT SIZE	UNIT WEIGHT	MASTER CARTON
LITE MANUAL	PLASTIC	13.8 X 13.8 X 23 CM	566 G	12 BOXED UNITS

STANDARD SUPPLY FORMAT

1 UNIT / COLOUR BOX | 12 BOXES / MASTER

One unit per colour box; 12 colour boxes per master carton. This is not a bulk-packed configuration.

POWER RATING

Use only a USB supply matching the marking on the finished unit.



PRODUCT & EXPORT PLAN

Declared boxed-product data and conservative upright-carton loading plan.

12

BOXED UNITS / CARTON

8.4

KG / MASTER CARTON

BOXED

DECLARED PACK FORMAT

STANDARD PRODUCT & ORDER DATA

ITEM NO.	PT-802
PRODUCT	Fly / Mosquito Light Trap - Lite
CONTROL FORMAT	Physical round power button + manual slider
MATERIAL	Plastic
PRODUCT SIZE	13.8 x 13.8 x 23 cm
UNIT WEIGHT	566 g
BOXED UNIT	689.5 g / boxed unit
PACKING	1 pc / colour box; 12 boxes / master carton
MASTER CARTON	58 x 44 x 25.5 cm
CARTON WEIGHT	8.4 kg
MOQ / LEAD TIME	504 pcs / 35 days / subject to order confirmation



MODEL CONTROL IDENTITY

Round button + manual slider



POWER INPUT

Supply must match the product marking

PACKING BASIS

One individually colour-boxed unit; 12 boxes per 58 x 44 x 25.5 cm master carton. Floor and pallet values below count master cartons and finished products.

EXPORT LOADING - MASTER CARTONS / PRODUCTS

1,200 x 1,000 x 144 mm pallet / container-door-height basis



PALLET

4 CTN / LAYER



20' GP

10 PALLETS



40' GP

20 PALLETS



40' HQ

20 PALLETS

CONTAINER	FLOOR LOADED	PALLETIZED
20' GP	400 CTN 4,800 pcs / plan 10 x 5 x 8	320 CTN 3,840 pcs / 10 pallets x 8 layers
40' GP	800 CTN 9,600 pcs / plan 20 x 5 x 8	640 CTN 7,680 pcs / 20 pallets x 8 layers
40' HQ	900 CTN 10,800 pcs / plan 20 x 5 x 9	720 CTN 8,640 pcs / 20 pallets x 9 layers

Floor plan uses upright 580 x 440 x 255 mm cartons. Door-height clearances: 240 / 240 / 290 mm for 20' GP / 40' GP / 40' HQ.

Pallet: 2 x 2 cartons/layer without overhang. Loaded heights: 2,184 / 2,184 / 2,439 mm; door clearances: 96 / 96 / 146 mm.

Nominal geometric plan only. Confirm carton tolerances, actual container door, payload, pallet condition, restraint and a physical trial load before shipment.

